



TYPICAL SECTION

NOTES

- 1 FINISHING, CURING, FORM WORK, PLACEMENT AND MATERIALS SHALL CONFORM TO WSDOT SPECS.
- 2 EXPANSION JOINTS SHALL BE PLACED ON 10 FOOT CENTERS.
- 3 EXPANSION JOINTS SHALL BE PLACED ADJACENT TO CATCH BASINS, INLETS AND AT POINTS OF TANGENCY ON STREETS, ALLEY AND DRIVEWAY RETURNS.
- 4 ALL JOINTS SHALL BE CLEAN AND EDGED.
- 5 FINISH SHALL BE LIGHT BROOM FINISH.
- 6 ALL CURB AND GUTTER SHALL BE PLACED ON A MIN. OF 2" OF CRUSHED SURFACING TOP COURSE COMPACTED AS SPECIFIED IN WSDOT STANDARDS AND SPECS.
- 7 1 1/2" EXPANSION JOINT BETWEEN CURB AND GUTTER AND THE SIDEWALK.
- 8 SEE 4-10 OPEN CURB FACE FRAME & GRATE INSTALLATION FOR 4' OF THICKENED CURB AT CATCH BASIN.

CEMENT CONCRETE CURB & GUTTER



6-2-004
date

3-6
number