



NOTES:

- ① FOUNDRY NAME, THIS SIDE TO CURB W/ARROW AND (DI) FOR DUCTILE IRON SHALL BE EMBOSSED ON TOP OF GRATE WITH 1/16" RECESSED LETTERS.
- ② SEATING OF GRATE SHALL BE ACCOMPLISHED BY ONE OF THE FOLLOWING:
A. 8 INTEGRALLY CAST PADS (1-1/2"x3/4"x1/8").
B. MACHINE BOTTOM SURFACE OUTSIDE A 17" DIA
- ③ MATERIAL USED SHALL BE DUCTILE IRON PER ASTM-A536, GRADE 80-55-06. ALL CASTINGS SHALL HAVE A BITUMINOUS COATING.
- ④ WHEN LOCKING GRATE REQUIRED HOLES WILL BE PROVIDED IN CASTING TO ALLOW FOR TWO 5/8" DIA STAINLESS STEEL SOCKET HEAD CAP SCREWS SO THAT NO PART OF HEAD PROTRUDES ABOVE TOP OF CASTING.
- ⑤ GRATE TO BE USED WITH FRAME SHOWN IN STANDARD DWG 4-5.

SLOTTED GRATE FOR CATCH BASIN OR INLET

I:\STANDARD_PLANS\STD4-6.DWG



8-2003
date

4-6
number